



FEATURES

- Long life elastomer diaphragm (ranges 4–6)
- Proven sealed piston sensor (ranges 7–10)
- · High quality snap action switch
- Field adjustable
- · Easily customized
- Quick delivery
- NEMA 4, 13

DIMENSIONS

18.0 (457.2mm) TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TURNEW DRIVER, THEN TURNEW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET SCREW WITH A SCREW DRIVER, THEN TO ADJUST SET SCREW WITH A SCREW DRIVER SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER SET POINT: LOOSEN SET SCREW WITH A SCREW DRIVER SET

SPECIFICATIONS

Set Point Range
Set Point Tolerance
Maximum Operating Pressure

Proof Pressure

Differential Current Rating

Media Connection Circuit Form Electrical Connection Diaphragm material

Cycle Life

10 – 4500 PSI (.69 – 289 Bar) ±5 PSI or 5% (.34 Bar) TDPS 8-10 5000 PSI (344 Bar)

TDPS 4-7 2000 PSI (138 BAR)

6,000 PSI (TDPS 4-7) 15,000 PSI (TDPS 8-10)

10 – 20%

5 A @ 250 VAC 5 A @ 30 VDC (Resistive)

See Order Chart Below for Options

SPST-NO or SPST-NC

Electrical Connection

W= Wire Leads L= Large DIN

See Order Chart Below for Options

Buna (Ranges 4–6)

Stainless Steel Piston (Ranges 7–10)

1 Million

ORDERING

Series TDPS4			Pressure Connection 3	Circuit Type C	[
TDPS4 TDPS5 TDPS6 TDPS7 TDPS8 TDPS9	10-40PSI 25-100PSI 50-200PSI 100-400PSI 250-1000PSI 500-2000PSI	(25PSI Center Set) (65PSI Center Set) (125PSI Center Set) (250PSI Center Set) (625PSI Center Set) (1250PSI Center Set)	3= 1/4" NPT 10= 9/16" x 18 SAE Male 2= 3/8" NPT Male 20= 3/4" x 16 SAE Male	C=SPDT / NO/NC	I

^{*}Contact factory for additional optional/custom modifications.

TDPS10 1200-4500PSI (2850PSI Center Set)