



# SEE THE INVISIBLE!

Better performance for one-tenth the cost of vision systems

DATA SHEET

## UVX-300 Luminescence Sensor



**Confirm manufacturing processes more reliably than vision systems that cost ten times more.** The patented technology in the UVX-300 luminescence sensor effectively detects UV luminescent materials and markers. The UV light source in the UVX-300 is directed towards a target and the visible light is reflected from the target back to the UVX-300. Because the UV luminescent materials and inks are invisible under a normal light spectrum, it is possible to mark products and parts without affecting their appearance. Some materials such as wood, grease and glue may contain UV luminescent materials naturally and in other cases the UV pigment may be added to the marking process.

### The UVX-300 was designed to meet several requirements.

First, the UVX-300 had to have a long range and be easy to program. Second, it had to have a quantitative display so the user can see what the sensor is registering. Third, the UVX-300 had to have exceptional resolution so it can effectively suppress the background on large targets and limit the detection to a contained area on small targets. Last, it had to provide all the output function variations in the same model to limit the number of models that have to be carried in stock.

### Our design team achieved those requirements.

- Unique numerical display lets you see the intensity of each reading. Now it's easy to refine processes and hysteresis.
- 3 to 6 times the range of any competing sensor. Won't get bumped or dirtied by target in the process.
- Only UV sensor with both auto-teach and manual calibration. Easy for low-skill operators, but able to be finely tuned.
- Adjustable UV light projection and high resolution allow pin-head size detection.
- Fast and convenient integration. In one sensor you get both analog and discrete output, auto-detect for PNP/NPN.
- Smallest and fastest on the market.

## Applications

The UVX-300 is used in many industrial applications to sense the following:

Grease	Oil	Glue
Labels	Epoxies	UV ink
Varnish	Wood	Textiles
UV Crayons	Paper	
Adhesive	Paint	

Although some applications may be similar to color or contrast sensing, the UVX-300 offers unmatched detection of UV fluorescent materials. There are also applications where the lack of luminescence is detected—for example, a break in a seal.

## UVX-300 Design and Features

- Long range sensing capability
- Auto-Teach and Manual functions
- Receiver gain and detection threshold display
- High resolution
- Programmable discrete and analog outputs
- Fast response time

**EMX**  
INDUSTRIES, INC.

1-800-426-9912 • [www.emxinc.com](http://www.emxinc.com)

**For quotes and questions,  
contact Applications  
Support:  
1-800-426-9912  
[salesupport@emxinc.com](mailto:salesupport@emxinc.com)**

# UVX-300 Luminescence Sensor

## Functions

OPERATING MODE	The UVX-300 is in operating mode in detect or undetect state.
REFLECTED UV LEVEL	Displays the relative reflection intensity.
THRESHOLD	Displays the preset detection level.
MANUAL PROGRAM MODE	Switches the UVX-300 to PROGRAM MODE.
SET THRESHOLD	Sets the detect level.
SET UV LED INTENSITY	Sets the UV LED intensity to LO, MED, HI.
SET HYSTERESIS LEVEL	Sets the un-detect level 1–9 steps below the detect level.
SET OUTPUT NO/NC	Sets the discrete output to NO or NC.
SET DETECTION EXTEND TIME	Extends the detect output by selected time.
SET LOCK/UNLOCK	Locks and un-locks the UVX-300 pushbutton controls.
TEACH MODE	Switches the UVX-300 to TEACH MODE.
TEACH DETECT	Sets the level of reflection at which the UVX-300 will detect the target.
TEACH UNDETECT	Sets the level of reflection so UVX-300 will not detect the target.
PNP/NPN	The micro controller detects and selects the required output configuration.

## Specifications

<b>Supply Voltage</b>	10–24 V DC
<b>Operational Current</b>	<60 mA
<b>Detection Range</b>	350mm
<b>Hysteresis</b>	10 settings
<b>On/Off Delay</b>	<150 $\mu$ s
<b>Switching Frequency</b>	6 kHz
<b>Output Pulse Stretch</b>	0–90 ms (10 steps)
<b>Discrete Output</b>	Auto-Detect PNP/NPN
<b>Analog Output</b>	0–5 V
<b>Output Function</b>	NO/NC selectable
<b>Short Circuit Protection</b>	Yes (outputs)
<b>Overload/Reverse Polarity Protection</b>	Yes (supply voltage)
<b>Remote Input</b>	LOCK/UNLOCK
<b>Signal Strength Display</b>	Two 7 segment digits
<b>Detection Threshold</b>	Two 7 segment digits
<b>Power Indicator</b>	7 segment display LED
<b>Detect Indicator</b>	Red LED
<b>Programming Indicator</b>	Green LED
<b>Data Retention</b>	EEPROM non-volatile memory
<b>UV Source</b>	370 nm UV LED life 100,000 hours
<b>Receiver Spectral Response</b>	350 to 1000 nm
<b>Operating Temperature</b>	–20 to 55°C
<b>Storage Temperature</b>	–20 to 70 C
<b>Housing</b>	Metal alloy
<b>Mechanical Protection</b>	IP67
<b>Connector</b>	M12 5 pin
<b>Size</b>	2.5" x 2" x 0.75"

## Values Stored in Non Volatile Memory

THRESHOLD, NO/NC, UV LED INTENSITY, Local LOCK/UNLOCK, DETECTION EXTEND TIME, HYSTERESIS LEVEL, TEACH DETECT, TEACH UNDETECT.

## Indicators

<b>7 Segment Display LED</b>	Power ON
<b>Red LED</b>	Detect
<b>Green LED</b>	Program

## Connector M12

<b>Pin 1</b>	Power 10 to 30 V DC
<b>Pin 2</b>	Discrete output PNP/NPN NO/NC
<b>Pin 3</b>	Ground
<b>Pin 4</b>	Analog output 0 to 5 V DC
<b>Pin 5</b>	Remote LOCK/UNLOCK input

## Certifications



**NOT INTENDED FOR USE IN PERSONAL SAFETY APPLICATIONS.**

## Ordering Information



**UVX-300**  
Luminescence Sensor

## Accessories



**UVX-300L50**  
50 mm focal lens



**UVX-300B**  
Bracket



**UVX-300C**  
5-meter cable with  
M12 5 pin connector



4564 Johnston Parkway • Cleveland, Ohio 44128  
Phone: 1-800-426-9912 or 216-518-9888 • Fax: 216-518-9884  
Email: salessupport@emxinc.com • Web: www.emxinc.com

